



Apreamare 28 Open

1 ENGINES

2 * VM 170 MD 704 LS power 170 mhp / 125 kW at 3800 rpm std

2 SPEED (knots)

	VM 170	
maximum speed (at full loaded displacement)	26,5	knots
velocità di crociera	23	knots

3 RANGE (nautical miles)

	VM 170	
maximum speed	125	n.m.
cruising speed	145	n.m.

4 MAIN SIZES

Loa = overall length (standard ISO 8666)	8,62	m.	28 ft. 3 in.
Lh = Hull length (standard ISO 8666)	7,62	m.	25 ft. 0 in.
Lg = waterline length (boat fully laden)	6,60	m.	21 ft. 8 in.
Max. beam	2,85	m.	9 ft. 4 in.
Depth under propellers (boat fully laden)	0,68	m.	2 ft. 3 in.
Displacement unladen	4	ton./lb.	8818
Displacement laden	5	ton./lb.	11023
Max.number of persons on board	8		
navigation category CE 2003/44	C		
certification modules	B + F + Aa (Sound Emission)		R.I.Na.

5 TECHNICAL DATA

Hull type : 13° of deadrise . Warped hull with spray rails			
H = Overall height from keel	2,60	m.	8 ft. 6 in.
H t = Minimum transport height from keel	2,60	m.	8 ft. 6 in.
P = pulpit	0	m.	0 ft. 0 in.
Fuel tanks capacity	400	lt./US gals.	106
Water tanks capacity	160	lt./US gals.	42

6 PERFORMANCE SPECIFICATIONS

the performance is estimated at the following conditions: standard version displacement of the yacht at full liquid load , clean hull , 25°C air temperature good weather conditions , 4 persons on board	5,6	ton./lb.	12346
overloading the yacht by	1	ton./lb.	2205
top speed decreases of	1	knot	

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant